

**Day / Twilight Protection:** aviation orange/white paint

**Night Protection:** 2,000 cd red lights (32 cd red side lights for A1)

### 1750 – 2200 ft. \*

11x L-864 medium intensity lights flashing in sync at 30 fpm

### 1400 – 1750 ft. \*

9x L-864 medium intensity lights flashing in sync at 30 fpm

### 1050 – 1400 ft. \*

7x L-864 medium intensity lights flashing in sync at 30 fpm

### 700 – 1050 ft. \*

5x L-864 medium intensity lights flashing in sync at 30 fpm

### 350 – 700 ft. \*

3x L-864 medium intensity lights flashing in sync at 30 fpm

### 150 – 350 ft. \*

1x L-864 medium intensity light  
2x or more L-810 flashing in sync with L-864 at 30 fpm

### 0 – 150 ft. \*

2x L-810 steady burning obstruction lights

### COMPLIANCE STANDARDS



#### FAA L-864

Medium intensity flashing (30 fpm) red obstruction light

>> [Click here for L-864 product information](#)



#### FAA L-810

Low intensity steady burning/ flashing (30 fpm) red obstruction light

>> [Click here for L-810 product information](#)

fpm flashes per minute



\* Including any appurtenances

A0

A1

A2

A3

A4

A5

A6

Guidelines only. Please refer to [FAA AC 70/7460-1L](#) or contact us for further information and guidance.